



iMist Monitoring Service

How to Guide

Button Combinations

Enable Wi-Fi

1. Hold the blue button until the LED lights up.
2. Release the button.
3. Follow the video instructions to connect your pump to Wi-Fi.



WIFI DETAILS

NAME: iMistSystem

PASSWORD: syst3mIMIST@%

PUTTING YOUR IMS PUMP INTO PAIRING MODE



NO LIGHT

Hold Until LED On



SOLID LIGHT

Release The Button



LIGHT TURNS OFF

Follow Video Instructions

Restart Device

1. Hold the button until the LED turns off.
2. Release it when the LED comes back on.
3. The LED will blink, indicating the pump is in restart mode.

LED Meanings

Startup

- LED illuminates for 10 seconds on power-up.
- Once off, the system is actively monitored.

Wi-Fi Connectivity

- **Connecting:** Delayed, recurring blink
- **Successful connection:** 10 fast blinks
- **Failure / Fallbacks activated:** Solid light; setup can be re-enabled once cleared
- **Switching to Wi-Fi setup mode:** Solid light; ready once cleared

YOUR LED LIGHT CONNECTIVITY STATUS GUIDE



CONNECTING

Delayed Recurring Blink



SUCCESSFUL CONNECTION

10 Fast Blinks



FAILURE/FALLBACK

Solid Light, Setup Re-enabled

Request Alarm Silencing

- For IMS-enabled units, we can remotely silence the alarm. Please call our office if you need an alarm on the pump to be silenced.